



MULTIMASTER MM 700 Max

Oscillating MultiTools - MM 700

Our best MultiTool for rapid work progress in interior construction and renovation with a bi-metal saw blade for wood, metal, and plastics.

Product number: 7 229 68 62 09 0

Details

- > Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- > StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- > 450 W FEIN high-performance motor: Durable, overload-protected, high-performance motor with high proportion of copper for higher cutting speed and ultra-rapid work progress.
- > Variable Speed: Constant speed even under load and variable electronic speed control.
- > Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > Industrial-strength cable: The 16 ft (5m) rubber-clad, industrial-quality cord gives you room to work.

Price includes

- ✓ 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- ✓ 1 tool case

Product feature

- ✓ Mechanical interconnection

Technical data

TECHNICAL DATA

Power consumption	450 W
Power output	250 W
Oscillations	10,000 - 19,500 opm
Tool mount	StarlockMax
Tool change	QuickIN
Range	2 x 2,0°
Cable with plug	16.4 [5] ft[m]
Weight	3.53 [1.60] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	85 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	96 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	97 dB 3 dB

Application examples

