



BLK 5.0

Nibbler up to 6 gauge

Powerful nibbler for heavy dismantling and cutting applications.

Product number: 7 232 31 12 63 4

Details

- > Powerful 1,200 watt motor for outstanding performance while maintaining excellent ergonomics.
- > Cuts over 90° edges, for example on guard rails or tanks.
- > Cutting direction can be adjusted in three 90° steps without the need for tools.
Optimum power-to-weight ratio.
- > Long tool life of punch and die.
- > Chip protection mesh on vent slots.
- > Handle can be rotated 180°.
- > 16 ft. [5 m] cable.
- > Stainless steel up to 13 gauge [2.5 mm].
- > Wide range of accessories.

Price includes

- ✓ 1 wrench
- ✓ 1 punch (3 13 09 110 00 4)
- ✓ 1 handle
- ✓ 1 die (3 13 09 107 00 0)
- ✓ 1 cutting head

Product feature

- ✓ Cutting direction

Application

Curve cuts



- ★ suitable
- ★★ well suitable

Technical data

TECHNICAL DATA

Power consumption	1,200 W
Power output	750 W
Strokes	750 spm
Cutting speed	4.3 [1.3] ft/min[m/min]
Steel 58,000 lbf/in ²	0.1969 [5.0] in[mm]
Steel 87,000 lbf/in ²	0.1299 [3.3] in[mm]
Steel 116,000 lbf/in ²	0.0984 [2.5] in[mm]
Non-ferrous metals up to 36,000 lbf/in ²	0.2756 [7.0] in[mm]
Cutting width	5/16 [8] in[mm]
Immersion Ø with die	1-11/16 [43] in[mm]
Radius of smallest curve (inside/outside)	3-1/2 [86] / 3-3/4 [94] in[mm]
Cable with plug	16.4 [5] ft[m]
Weight	8.38 [3.80] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	85 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	96 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	100 dB 3 dB
Vibration value 1 αhv 3-way Measurement uncertainty of the measured value Kα	10 m/s ² 1,5 m/s ²



FEIN

Application examples

