4-Pc CNC Collection No. **AMS-316**



CNC 4-PC Simulated MDF Shaker Door Router Bit Set













INDUSTRIAL

CNC 4-PC SIMULATED MDF **SHAKER DOOR SET**

1/4" & 1/2" SHANK

Designed specifically for creating simulated MDF shaker doors

Congratulations on the purchase of your new Amana Tool® CNC set, a premier CNC router bit set.



Material Key Chart:









Ouestions? Call the Technical Hotline

(800) 445-0077 +1 (631) 752-1300



Free Vectric Master .tool File Database can be found on www.amanatool.com/vectric

A Vectric File Warning:

The Vectric .tool file should only be used in conjunction with the Amana Tool® item number specified. Using this file with other brands is dangerous to the operator and CNC machine.

*RPM: Revolutions Per Minute **IPM: Inches Per Minute





SPIRAL FLUTE PLUNGE

Solid Carbide, Down-Cut

Diameter: 1/8" **Cutting Height:** 1/2" Shank: 1/4"

Overall Length:

Flutes: 2 Flute

CNC Running Parameters:

RPM: 18.000* Feed Rate: 40" IPM** Ramp Down Rate: 20" IPM** Max Depth Per Pass: 1 x Diameter







#45408-3

SPIRAL FLUTE PLUNGE

Solid Carbide, Down-Cut

Diameter: 1/4" **Cutting Height:** 3/4" Shank: 1/2"

Overall Length:

Flutes: 3 Flute

CNC Running Parameters:

RPM: 18.000* Feed Rate: 800" IPM**

Ramp Down Rate: 266" IPM**

Max Depth Per Pass: 3/4"











#RC-1108

60° INSERT CARBIDE V-GROOVE

#RCK-56

GENERAL PURPOSE INSERT SOLID CARBIDE KNIFE

Diameter: 1-1/16"

Cutting Height: 29/32"

Shank: 1/2"

Overall Length: 2-15/32"

Flutes: 1 Flute

CNC Running Parameters:

RPM: 18.000*

Feed Rate: 40" IPM**

Ramp Down Rate: 40" IPM**

Max Depth Per Pass: 1/4"











INSERT SPOILBOARD

#RCK-459

4-SIDED SOLID CARBIDE INSERT KNIFE

Diameter: 12-1/2"

Cutting Height: 53/64"

Shank: 1/2"

Overall Length: 2-19/32"

Wings: 2 Wing

CNC Running Parameters:

RPM: **18,000***

Feed Rate: 350" IPM**

Ramp Down Rate: 175" IPM**










4 STEPS TO CREATE SIMULATED MDF DOORS

Cuts Flat Panels of Door





Cleans Flat Panels Corners

