



ASCD 18-200 W4

Cordless Impact Wrench/Driver

Cordless impact driver with brushless motor and 6 torque settings. For universal screw applications including self-drilling screws.

Product number: 7 115 07 61 09 0

Details

- Brushless FEIN PowerDrive motor with 30% greater efficiency and longer service life.
- 6-Step electronic torque setting prevents shearing of screw heads.
- > 10% higher torque in reverse to release extremely tight bolts.
- MultiVolt-interface. Cordless tool can be used with all FEIN li-ion batteries (12-18 V).
- > 1/4 in hexagonal socket for mounting bits and Allen key inserts.
- > Robust, solid metal impact gearbox.

- > Touch guard on drive head.
- > Compact design.
- > 600 screw applications (11/16 in [M18]) with one battery charge (6 Ah).
- One charger for all voltage classes of FEIN Li-ion batteries.
- > The battery capacity can be read directly on the battery.
- > FEIN SafetyCell technology. Protects the battery and the machine from overloading, overheating and deep discharge.

Price includes

- ✓ 2 rechargeable batteries (Li-ion)
- 1 bit garage

1 rapid charger ALG 80

1 tool case





Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

| Battery voltage | 18 V | Sound pressure level LpA Measurement uncertainty of the | 93,8 dB 3 dB |
|------------------------|---------------------------------|--|------------------|
| Battery capacity | 6 Ah | measured value KpA | |
| Battery compatibility | Li-ion / HighPower Li- ions | Sound power level LWA Measurement uncertainty of the measured value KWA | 104,8 dB 3 dB |
| Battery interface | MultiVolt | Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak | 114,5 dB |
| Motor | brushless | | 3 dB |
| No load speed | 0 - 1,500 rpm | Vibration value 1 α hv 3- way Measurement uncertainty of the measured value K α | ah 12,9 m/s² |
| Blows per minute | 0 - 3,000 rpm | | 1,5 m/s² |
| Max. torque | 1859 [210] in/lbs[Nm] | | |
| Torque steps | 6 | | |
| Tool mount | 1/4 in Hexagon socket | | |
| Wood screw dia. | 3/8 [8] x 7-7/8 [200] in[mm] | | |
| Weight incl. battery | 3.75 [1.70] lbs[kg] | | |
| Weight without battery | 2.20 [1.00] lbs[kg] | | |



Application examples



