



Cordless MULTIMASTER AMM 700 Max Select

Cordless oscillating multi-tool

Our best cordless MultiTool for ultra-rapid work progress with interior construction and renovation in the variant without a battery and charger – with a bi-metal saw blade for wood, metal, and plastics.

Product number: 7 129 34 62 09 0

Details

- > Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- > StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- > 18 V FEIN PowerDrive motor: Especially powerful, virtually wear-free brushless motor with high efficiency, extremely high load handling and long service life.
- > Variable Speed: Constant speed even under load and variable electronic speed control.
- > Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > SafetyCell technology: Perfect protection from overload, overheating and deep discharge thanks to Li-ion batteries with individual cell monitoring.
- > Dust protection grille - protects tool from aggressive dust.
- > The battery capacity can be read directly on the battery.

Price includes

- ✓ 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152) ✓ 1 tool case

Product feature

- ✓ Mechanical interconnection



Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / HighPower Li-ions
Battery interface	MultiVolt
Oscillations	10,000 - 19,500 opm
Tool mount	StarlockMax
Tool change	QuickIN
Range	2 x 2,0°
Weight without battery	2.43 [1.10] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	83 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	94 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	97 dB 3 dB

Application examples

